

info@pgsintl.com
sales@pgsintl.com



PGS INTERNATIONAL TUNISIA
6 Rue El Farabi, ZI Saint Gobain,
Côté Voie Ferrée 2014 Mégrine - Tunisia
☎ : +216 31 376 565 📠 +216 31 376 568

PGS INTERNATIONAL ALGERIA
Cite SAID HAMDINE Logement
195/574, Type A, No 04, Group
Propriété 01, Section 05, BIR MOURAD RAIS
Alger-Algerie

PGS INTERNATIONAL MOROCCO
La residence les Jardins de Ain Sebaa,
Prato/imm 8 n°12, Casablanca - Morocco

© 2023 PGS. All rights reserved PGS-COM-BR-01 Rev01

PGS INTERNATIONAL
Solutions | Additives Injection Systems

www.pgsintl.com



One-Stop Solution

Our additive injection skids are typically used for metered, small-volume additives such as product quality improvement, and are designed to interface with preset controllers electronic registers.

Available with a variety of tank sizes, single or double wall tanks, vertical or horizontal and Flame Shield or Fire Guard tanks. Options include stainless steel pump in stade of carbon steel, handheld controller, tote-tank kit, and dual or triple point injection (consult sales for full list of options).

Benefits

PGS offers a complete customized skid package with a range of reliable measurement products and components, depending on specific requirements, selected from reliable manufacturers. PGS manufactures complete additive systems for petroleum and petrochemical applications worldwide.

All PGS skids are built to meet specific customer requirements.

A modular design ensures the product can be easily packed and shipped to the customer's site via truck, rail, or cargo ship. PGS skids are also designed to minimize reassembly and startup expense once the skids are delivered on site.

Design features

Mechanical components

- Inlet ball valve.
- Line y-strainer.
- Pressure relief valve.
- Pressure gauge.
- Outlet isolation ball valve.
- Pump outlet check valve assembly.
- Racks are galvanized or painted white.
- Single pump or dual (redundant) pump configuration.
- Interconnecting piping, tubing.
- Level gauge.



Electrical components

Explosion-proof electrical enclosure with circuit breaker, dual motor starter, Hand-Off-Auto switch, A/B selector switch, A/B run lights, & reset buttons.

- Pump sequential PLC.
- Level switches.
- Level transmitter.
- A sounder/beacon for alarm signal.
- Interconnecting conduit and wiring.

Available sizes

- Up to 10 m³ tank size available.
- Tote tank or barrel kits available.

Flow rates

Standard flow rates from 0.2 - 2m³/h.

Strainer / Air release

In-line strainers / air eliminators are located at the highest elevation in the system, where gases breakout, to protect the metering system against dirt / other contaminants / air introduced by hoses.

Options :

- Each pump starts will alternate between Pump A & Pump B Switch to alternate pumps if one fails Time delay shut-off.
- High pressure pump switch.
- Temperature product alarm.
- Additive injectors.
- Totaliser.